

Jockimo™

Advanced Architectural Products

PRODUCT ARCHITECTURAL SPECIFICATION - Antique Mirrors

GENERAL PRODUCT DESCRIPTION: Our antique mirrors are custom cut to each customer's specifications and are available in the following thicknesses: 1/8", 3/16", 1/4" and thicker for some finishes on special request. Mirror edging options include: clean cut (CC), seamed (SE), or polished. Beveled antique mirrors may contain a bevel width ranging from 0.25" to 1.5".

PRODUCT MANUFACTURING: Our antique mirror product is manufactured utilizing a galvanic plating process with layers of tin, copper, silver, and protective paint. For more specific manufacturing details, please reference the "Silvered Flat Glass Mirror Certification" document. Additional fabrication may include edging, beveling, safety-tape backing, and grooving.

PRODUCT STANDARDS: Our antique mirror product meets the industry product standard (ASTM C1036-21). Consumer Product Safety Commission (CPSC) Category 1 and 2. Safety tape backing is available in both Category 1 and 2 strengths that meet industry impact standards (ANSI Z97.1).

WARRANTY: Our antique mirrors are guaranteed against silver and black edge defects when installed using Gunthers Mirror Mastic only. For additional details, please reference the Jockimo Limited Warranty document.

INSTALLATION: Antique mirrors may be installed with mechanical fasteners (e.g., clips, J-channel, L-bar) or with Gunthers Mirror Mastic. For additional details, please reference the Jockimo Cleaning & Maintenance Information document.